



GROSS WEIGHT	LENGTH	TARE +/- 3% (Kg/Lbs)
Kg	(m)	3 Decks
51000	18.0	19000

TECHNICAL CHARACTERISTICS

- Ø **Chassis:** High tensile steel - I beam section – more cross members – completely hot galvanized.
- Ø **Axles:** twin fixed 12000 Kg capacity.
- Ø **Brakes:** drum Ø 420x200 mm with brake linings asbestos free.
- Ø **Braking system:** pneumatic with 2 lines according to European standard with 2 channel ABS.
- Ø **Parking Brakes:** spring brakes with pneumatic controls.
- Ø **Suspensions:** mechanical with multi-leaf springs.
- Ø **Wheels:** disc 20.00 x 8.0 and M spigot.
- Ø **Tires:** 12.00R20 twin.
- Ø **King Pin:** 2" or 3,5" demountable from below.
- Ø **Landing legs:** two speed heavy duty.
- Ø **Body:** box unit for small animals completely hot galvanized - 3 opening decks with foldable Aluminium traps - opening roof with foldable Aluminium traps - wide toolboxes underneath the chassis - internal and external working lights – rear Aluminium loading ramps mechanical balanced
- Ø **Partition gates:** in Aluminium.
- Ø **Side windows:** closed by sliding panels.